

# LEISEGANG OptiK® Model 2

## Optimized Digital Imagery Paired with Exceptional Optics

LEISEGANG celebrates more than 60 years as a world leader in colposcope design and production, recognized for German precision, clarity and durability. Specially selected, hand-polished and hand-set glass optics are used in all LEISEGANG OptiK colposcopes. The optical brilliance achieved through our precision manufacturing process is unparalleled.



24 MegaPixel Canon Rebel T6i DSLR

### Features

- OptiK scope head with convergent optical beams
- Par-focal, 3-step magnification (3.75x, 7.5x, 15x)
- Bright, white, energy-efficient Light-Emitting Diode (LED) light, stable color spectrum (similar to daylight) provides highly improved contrast and better clarity
- LED life > 20,000 hours or 20 years<sup>1</sup> for lasting performance
- Independently adjustable oculars and diopters
- Measurement reticules for quick lesion size assessment
- Gross/fine focus and height adjustment
- EMR compatibility - captures jpgs to add to EMR system
- Available in three unique base configurations

### Specifications

- Working Distance: 300 mm
- Field of View: 19 mm to 76 mm
- Depth of Field: 2 mm to 8 mm
- Height: 50–60 inches (varies by base)
- Weight: 60 lb (without base; total 100–129 lb varies by base)
- Base Diameter: 28 in.
- 110 V power supply



### Available Base Configurations



UPRIGHT



BALANCE-O-MATIC



SWING ARM

All marks bearing the symbols TM and © are trademarks and registered trademarks of CooperSurgical, Inc., except where noted.

Canon® is a registered trademark of Canon, Inc.

<sup>1</sup> Average daily use of four hours.

**CooperSurgical**

203.601.5200 | 800.243.2974 | [coopersurgical.com](http://coopersurgical.com) | 95 Corporate Dr. | Trumbull, CT 06611

©2017 CooperSurgical, Inc.

81924 Rev. 1/18