



MATERIAL SAFETY DATA SHEET

(form according to EEC Directive 93/112/EC)

NAME : *LITHIUM-ION RECHARGEABLE BATTERIES*

1 - IDENTIFICATION (of the product and the supplier)

1.1. Product

Rechargeable battery

yes	X
no	

Trade name and model : *LITHIUM-ION RECHARGEABLE BATTERIES*

IEC designation :

Models : MP series MP 144350 - MP 174865 - MP 176065
VL series VL34570 – VL34480

Electrochemical system :

Electrodes	Negative electrode Carbon	Positive electrode Lithium cobaltite (LiCoO ₂)*
Electrolyte	Solution of lithium hexafluorophosphate (LiPF ₆) in a mixture of organic solvents**	
Nominal voltage	3.6 Volt	

* Equivalent name : lithiated cobalt oxide

** Ethylene Carbonate (EC) + DiMethyl Carbonate (DMC) + DiEthyl Carbonate (DEC)
+ Ethyl Acetate (EA).

1.2 - Supplier

Name : SAFT

Address : **for MP series**

Rue Georges Leclanché - BP 1039 86060
Poitiers Cedex 09 – France
Phone : +33 (0)5 49 55 48 48
Fax : +33 (0)5 49 55 48 50

for VL series

313 Crescent Street
Valdese, NC USA
+1 (0)828-874-4111
+1 (0)828-874-2431

1.3.- Emergency contact :

for MP series : Plant Manager Phone: +33 - (0)5 49 55 48 48

for VL series : CHEMTREC Phone: +1 - 800 424-9300

for information : +1-828-874-4111 or +1-828-438-3287

2 - COMPOSITION (typical weight percentages of basic material)

Metals	%	Plastics	%	Others	%
Steel, Copper, Aluminum	31	Polypropylene	10	- Lithium cobaltite - Carbon - Organic solvents - Salts - Lithium metal	29 16 13 1 0

3 - HAZARDS IDENTIFICATION

3.1 - Physical :

The Lithium-Ion rechargeable batteries described in this Material Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the Manufacturer.

Under normal conditions of use, the solid electrode materials and liquid electrolyte they contain are non-reactive provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) leading to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

MP batteries are fitted with a safety vent for protection incase of excessive internal pressure and/or temperature.

3.2 - Chemical :

Classification of dangerous substances contained into the product as per directive 67/548/EEC

Substance	CAS N°	Chemical symbol	Melting Point	Boiling Point	Classi fication		
					Exposure limit	Indication of danger	Special risk (1)
12190-79-3	LiCoO ₂	> 1000°C	N/A	0.1 mg/m ³ OSHA		R22 R43	S2 S22 S24 S26 S36 S37 S43 S45
EC : 96-49-1 DMC : 616-38-6 DEC : 105-58-8 EA : 141-78-6	Organic solvents (DC-DMC DEC-EA)	EC : 38°C DMC : 4 °C DEC : -43°C EA : -84°C	EC : 243°C DMC : 90°C DEC : 127°C EA : 77°C	None established OSHA	Flammable	R21 R22 R41 R42/43	S2 S24 S26 S36 S37 S45
21324-40-3	LiPF ₆	N/A (decomposes at 160°C)	N/A	None established OSHA	Irritant Corrosive	R14 R21 R22 R 41 R43	S2 S8 S22 S24 S26 S36 S37 S45

1 - Nature of special risks :

R 14	Reacts with water
R 21	Harmful in contact with skin
R 22	Harmful if swallowed
R 41	Risk of serious damage to the eye
R 42/43	May cause sensitization by inhalation and skin contact
R 43	May cause sensitization by skin contact

2 - Safety advices :

S 2	Keep out of reach from children
S 8	Keep away from moisture
S 22	Do not breathe dust
S 24	Avoid contact with skin
S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical attention
S 36	Wear suitable protective clothing
S 37	Wear suitable gloves
S 45	In case of incident, seek medical attention.

4 - FIRST AID MEASURES

In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out fumes/gases.

In all case, seek medical attention.

Eye contact : Flush with plenty of water (eyelids held open) for at least 15 minutes.

Skin contact : Remove all contaminated clothing and flush affected areas with plenty of water and soap for at least 15 minutes.
Do not apply greases or ointments.

Ingestion : Dilute by giving plenty of water and get immediate medical attention. Assure that the victim does not aspirate vomited material by use of positional drainage.
Assure that mucus does not obstruct the airway.
Do not give anything by mouth to an unconscious person.

Inhalation : Remove to fresh air and ventilate the contaminated area.
Give oxygen or artificial respiration if needed.

5 - FIRE-FIGHTING MEASURES

Fire and explosion hazard : The battery can leak and/or spout vaporized or decomposed and combustible electrolyte fumes in case of exposure above 70°C resulting from inappropriate use or the environment.
Possible formation of hydrogen fluoride (HF) and phosphorous oxides during fire.
Li PF₆ salt contained in the electrolyte releases hydrogen fluoride (HF) in contact with water.

Extinguishing media : *Suitable :* CO₂,
Dry chemical or Foam extinguishers
Not to be used : Type D extinguishers

Special exposure hazards : Following cell overheating due to external source or due to improper use, electrolyte leakage or battery container rupture may occur and release inner component/material in the environment.

Eye contact : The electrolyte solution contained in the battery is irritant to ocular tissues.

Skin contact : The electrolyte solution contained in the battery causes skin irritation.

Ingestion : The ingestion of electrolyte solution causes tissue damage to throat and gastro/respiratory tract.

Inhalation : Contents of a leaking or ruptured battery can cause respiratory tract, mucus, membrane irritation and edema.

Special protective equipment : Use self-contained breathing apparatus to avoid breathing irritant fumes.
Wear protective clothing and equipment to prevent body contact with electrolyte solution.

6 - ACCIDENTAL RELEASE MEASURES

The material contained within the batteries would only be expelled under abusive conditions.

Using shovel or broom, cover battery or spilled substances with dry sand or vermiculite, place in approved container (after cooling if necessary) and dispose in accordance with local regulations.

7 - HANDLING AND STORAGE

The batteries should not be opened, destroyed nor incinerated since they may leak or rupture and release in the environment the ingredients they contain.

Handling : Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e. metal) goods. Do not directly heat or solder. Do not throw into fire. Do not mix batteries of different types and brands. Do not mix new and used batteries. Keep batteries in non conductive (i.e. plastic) trays.

Storage : Store in a cool (preferably below 30°C) and ventilated area away from moisture, sources of heat, open flames, food and drink. Keep adequate clearance between walls and batteries. Temperature above 70°C may result in battery leakage and rupture. Since short circuit can cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do not jumble them.

Other : Follow Manufacturers recommendations regarding maximum recommended currents and operating temperature range.

Applying pressure on deforming the battery may lead to disassembly followed by eye, skin and throat irritation.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : *Not necessary under normal use.*
In case of battery rupture, use self contained full-face respiratory equipment.

Hand protection : *Not necessary under normal use.*
Use gloves if handling a leaking or ruptured battery.

Eye protection : *Not necessary under normal use.*
Wear safety goggles or glasses with side shields if handling a leaking or ruptured battery.

Skin protection : *Not necessary under normal use*
Use rubber protective working in case of handling of a ruptured battery.

9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance : (Physical shape and color as supplied)
Small prismatic metal cylinders, hermetically sealed and fitted with an external plastic sleeving.

9.2 Temperature range :

	Continuous	Occasional
in storage	+ 30°C max	-40/+70°C
during discharge	-30/+70°C	-40/+70°C
during charge	0/+50°C	0/50°C

9.3 Specific energy :

≈ 130 Wh/kg

(Note : Wh = Nominal voltage x Rated Ah as defined in IEC Standard N° 285. Kg = Average battery weight)

9.4 Specific pulse power : ≈ 300 Wh/kg

9.5 Mechanical resistance : As defined in relevant IEC Standard

9.6 Other :

10 - STABILITY AND REACTIVITY

Conditions to avoid : Heat above 70°C or incinerate.
Deform, mutilate, crush, pierce, disassemble.
Short circuit.
Prolonged exposure to humid conditions.

Materials to avoid : N/A

Hazardous decomposition products :

Corrosive/Irritant Hydrogen fluoride (HF) is produced in case of reaction of *lithium hexafluorophosphate (LiPF₆)* with water..

Combustible vapors and formation of Hydrogen fluoride (HF) and phosphorous oxides during fire.

11 - TOXOLOGICAL INFORMATION

SAFT MP and VL Lithium-Ion rechargeable batteries do not contain toxic materials.

12 - ECOLOGICAL INFORMATION

When properly used or disposed, SAFT MP and VL Lithium-Ion rechargeable batteries do not present environmental hazard.

13 - DISPOSAL CONSIDERATIONS

Dispose in accordance with applicable regulations which vary from country to country.

(In most countries, the trashing of used batteries is forbidden and the end-users are invited to dispose them properly, eventually through not-for-profit profit organizations, mandated by local governments or organized on a voluntary basis by professionals).

Lithium-Ion batteries should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal.

13.1 . Incineration : Incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.

13.2 . Landfilling : Leachability regulations (mg/l)

Component	Leachability	EC limit	EPA	Other*
Iron	100			5
Nickel	500	2		0.5

* applicable to France

13.3 . Recycling : Send to authorized recycling facilities, eventually through licensed waste carrier.

14 - TRANSPORT INFORMATION

14.1 United Nations : UN N° 3090
 Classification 9
 Packaging ICAO 903 for Air Transport
 IMDG for Sea Transport

14.1 International conventions :

Air	IATA	Yes
Sea	IMDG	Yes
Land	ADR (road)	Yes
	RID (rail)	Yes

14.3 Other : in the USA Code of Federal Regulations (49 CFR Ch. 1 § 173-185)



15 - REGULATORY INFORMATION

The transport of rechargeable Lithium-ion batteries is regulated by the United Nations as detailed in the *"Model Regulations on the Transport of Dangerous Goods Ref. ST/SG/AC.10/1 Revision 11 1999"*.

Depending on their lithium equivalent weight content, and ability to pass safety tests defined by UN in the *"Recommendations on the Transport of Dangerous Goods Chapter 38.3 Manual of Tests and Criteria Ref. ST/SG/AC. 10/11 Third Revised Edition 1999"*, the Lithium-ion cells and the battery packs may or may not be assigned to the UN N° 3090 Class-9 that is restricted for transport.

Individual Lithium-ion cells and battery packs with respectively less than 1.5 and 8 gram of Lithium Equivalent Weight content (case of the MP 14 43 50 and MP 17 48 65 batteries; and VL34570 and VL34480 batteries) are not restricted for transport (1.0. Ah of Nominal Capacity = 0.3 gram of LEW).

16 - OTHER INFORMATION / DISCLAIMER

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

Saft does not accept liability for any loss or damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. Saft does not offer warranty against patent infringement. Additional information is available by calling the telephone number above designated purpose.

First Edition Date 07/2000

Signed _____
Lithium Product Manager